

PACKING MACHINE AM 600



Basic equipment

- 1. CURVED BELT CONVEYER**
 - 1.1 Conveyor belt**

- 2. BELT CONVEYER WITH CONTROL UNIT**

consisting of:

 - 2.1 Conveyer FB 1211**
 - 2.2 Conveyer belt FG 31**

5. UNIT COUNTER VZE



The electronic unit counter gives information about the overall production (8-figure), the daily production (7-figure) and the number of items per unit (a row of boxes 3-figure). The last shown values are, by means of a built-in memory, stored for approximately 8 weeks and are again available after switching on the unit counter.

The unit is equipped with a laser counter

TECHNICAL DATA

Processible materials

Cardboard from	200 - 1.500 g/m ²
E + B-Flute	up to 4 mm thick

Formats:

folded boxes

Length: max. 600 mm
min. 50 mm

Width: max. 600 mm
min. 30 mm

Construction: straight line boxes
crash lock bottom boxes
Double wall boxes
4 and 6 corner boxes
Special contractions possible

Production speed: 10 - 500 m/min

Installation values

Power Supply approx. 1 KVA

Power Consumption approx. 500 - 600 Watt

Weight approx. 300 kg

ERECTED DIMENSIONS

Length approx. 365 cm

Width approx. 190 cm

Working height approx. 80 cm

